

SPECIFICATIONS

OPERATION:

The exclusive Squaring-Arm pulls a case from the magazine, squares it, then grips the case on three sides as the flap kicker kicks up the trailing minor flap. The carriage then advances, folding the lead minor flap. It then transfers the case to the drive side belts and the major flaps are closed. The case is then sealed.

FEATURES:

- * Welded Steel Frame
- * Easy To Operate
- * Simple Changeover
- * On - Demand or continuous Operation

SPEED:

Up to 20 c.p.m.
(based on case characteristics)

AIR REQUIREMENTS:

80 p.s.i.,
approx. 3/4 cubic foot/cycle

ELECTRICAL REQUIREMENTS:

120 Volts VAC single phase
10 AMPS

MAGAZINE Capacity:

Up to 107 cases – single wall,

MACHINE DIMENSIONS:

Overall Height: 63 1/2"
Overall Width: 87 1/2"
Overall Length: 109 "

TABLE HEIGHT:

Standard: 24-1/4" to 36"
Optional: 22-1/2"

CASE SIZE RANGE:

OPTIONAL: Consult factory

STANDARD **

| | <u>Min</u> | <u>Max</u> |
|---------|------------|------------|
| Length: | 8" | 18" |
| | 203.2/mm/ | 457.2/mm/ |
| Width: | 6" | 16" |
| | 152.4/mm/ | 406.4/mm/ |
| Height: | 4" | 15" |
| | 101.6/mm/ | 381.0/mm/ |

****THE STANDARD MACHINE MAY NOT ACCOMMODATE CERTAIN CASE SIZE COMBINATIONS (i.e. SHORT HEIGHT AND LONG LENGTH AND WIDTH). CONSULT THE FACTORY.**

AVAILABLE Options:

- * Pack Station (PS-2)
- * Quick Change Pack Station (PS-100-2A)
- * Electric Signal On-Demand (air signal on-demand standard.)
- * Power Driven 175 cases with extended magazine